

Quality Solution For All Growers




WASH & WAX UNIT

From ***K W Automation***



Electronically Regulated Wax Pump



- ▶ **Numerous** brush total & brush width combinations to meet Grower needs.
- ▶ **Storage tank** for wax solution.
- ▶ **Unique** chain driven brushes for quieter operation.
- ▶ **Height Adjustable** legs for smooth flow of fruit line.
- ▶ **Durable** powder-coated for extra protection.
- ▶ **Gentle** handling for your fruit.
- ▶ **Easy** access to fruit.

The **Wash & Wax Unit** is enclosed with an easily accessed divided collecting tray with outlets fitted for both washing and waxing operations.

One wash nozzle and soft brushes gently wash the fruit. Flicker bars agitate the brushes to shake off excess water. As an option fruit may also pass over foam rollers to further remove excess water.

The fruit then proceeds through into the waxing section. Spray nozzles spray the fruit while the soft brush rollers aid in the total coverage.

Wax is dispersed via a diaphragm pump and coupled with a timer may be electronically regulated for different grower requirements and to keep wax wastage to a minimum.



Manufactured By:

K W Automation

PO Box 121, Old Bowling Green Rd
Palmwoods, Queensland 4555 Australia
Int (61) - (07) 5445 9549 - Fax (07) 5445 0499
Web Site: www.kwautomation.com.au

Wash & Wax Unit	Specifications
Capacity of Motor	.18 kW (1/4 HP) 10 Brush Unit
Power Supply Req'd	240V or 415V
Length of 10 Brush Unit	1.470 Metres
Width of 10 Brush Unit	.750 Metres (460mm Wide Brush)
Height of 10 Brush Unit	1.430 Metres
No. of Brushes per Unit	10,12,14,16 or 20
Width of Brushes	460mm,600mm or 900mm
Std Brush Speed	116 R.P.M
No. of Wash Spray Nozzles	1
No. of Wax Spray Nozzles	1

